



- | | | | |
|----|--|-----|---|
| 1. | 2x6 WD. STUD WALL @ 16" O.C. | 6. | FURR OUT EXTERIOR WALL WITH 2x4 WOOD STUDS FOR WATER PIPING. |
| 2. | PARTIAL HEIGHT WALL. INSTALL UNISTRUT AT EACH END AND 4'-0" O.C. MAX. REFER TO DETAIL 6/A01. | 7. | PROVIDE IN-WALL CHASE FOR SODA LINES. WRAP OPENING WITH FRP. REFER TO PLUMBING DRAWINGS. |
| 3. | 2 x 4 FUR OUT WALL AT ELECTRIC PANELS, REFER TO ELECTRICAL DRAWINGS. | 8. | PARTIAL HEIGHT WALL LOCATION UNDER SERVICE COUNTER. REFER TO COUNTER SECTION. |
| 4. | INSTALL TELEVISION AND MOUNTING BRACKET. PROVIDE IN-WALL BLOCKING. COORDINATE FINAL LOCATION WITH DECOR. VERIFY WITH OWNER DURING BIDDING PROCESS. | 9. | PARTIAL HEIGHT WALL. INSTALL UNISTRUT AT EACH END AND 4'-0" O.C. MAX. REFER TO DETAIL 6/A102. |
| 5. | PREPARE STAINLESS STEEL SHEET OVER 1/2" CEMENT BOARD | 10. | PARTIAL HEIGHT WALLS. REFER TO DETAIL 8/A102. |

- | | | | |
|----|--|-----|--|
| A. | VERIFY ALL UNMARKED WALLS WITH ARCHITECT. | R. | VERIFY ALL EXTERIOR WALLS AND REFER TO STRUCTURAL DRAWINGS FOR STUD TYPE AT HOOD. |
| B. | GENERAL CONTRACTOR TO PROVIDE ALL WALLS INDICATED ON FLOOR PLAN. | S. | ALL INTERIOR WALLS ARE 3 1/2" WOOD STUDS U.N.O. |
| C. | PROVIDE 2x6 WOOD BLOCKING IN PARTITIONS TO SUPPORT ALL CASEWORK, DOOR WALL STOPS, ELECTRICAL AND MECHANICAL DEVICES, AND FIRE EXTINGUISHERS. | T. | VERIFY LOCATION OF ALL EQUIPMENT AND VERIFY SIZES, WALL OPENINGS, AND SUPPORT REQUIREMENTS WITH MANUFACTURER. PROVIDE REINFORCEMENT AS REQUIRED BY MANUFACTURER. |
| D. | ELECTRICAL CONTRACTOR TO COORDINATE LOCATIONS OF MECHANICAL EQUIPMENT AND FIRE PROTECTION PRIOR TO STARTING WORK. | U. | ALL DOORS TO BE LOCATED 4" FROM ADJACENT WALL OR COUNTER, OR CENTERED IN WALL UNLESS OTHERWISE NOTED. |
| E. | GENERAL CONTRACTOR TO PATCH ALL ROOF PENETRATIONS MADE BY THIS PROJECT WITH OWNER'S ROOFING CONTRACTOR. | V. | ALL WALLS TO RECEIVE LAMINATE OR WOOD PLANKS MUST HAVE PLYWOOD BACKING IN LIEU OF GYP. BD. COORDINATE LOCATION WITH INTERIOR FINISHERS. |
| F. | GENERAL CONTRACTOR TO PROVIDE ALL ROOF PATCHING AROUND MECHANICAL EQUIPMENT. VERIFY ROOF WARRANTY REQUIREMENTS WITH OWNER. | W. | DO NOT INSTALL PLYWOOD ON WALLS TO RECEIVE TILE. REFER TO WALL TYPES FOR SPECIFIC SHEATHING REQUIREMENTS. |
| G. | SEE WALL SECTIONS AND DETAILS. | X. | 2x2 FLOOR HEIGHT STAINLESS STEEL CORNER GUARDS ON ALL OUTSIDE CORNERS IN KITCHEN. PROVIDED AND INSTALLED BY GC. |
| H. | SEE INTERIOR FINISH NOTES FOR FINISH SPECIFICATIONS AND PLAN. | Y. | THE GENERAL CONTRACTOR IS TO VERIFY SIZE, QUANTITY AND LOCATION OF FIRE EXTINGUISHERS WITH LOCAL FIRE MARSHAL PRIOR TO INSTALLATION. REFER TO LIFE SAFETY PLAN. |
| I. | SEE SHEET A103 FOR REFLECTED CEILING PLAN. | Z. | 2x BLOCKING TO BE PROVIDED AT ALL SINKS, GRAB BARS, MIRRORS, DISPENSERS, AND HAND DRYERS PER MFR. SPECIFICATIONS. |
| J. | SEE SHEET A101 FOR DOOR SCHEDULE. | AA. | DO NOT SCALE OFF PLANS, CALL THE ARCHITECT FOR ADDITIONAL DIMENSIONAL INFORMATION IF REQUIRED. |
| K. | VERIFY ALL OWNER SUPPLIED EQUIPMENT BEFORE ROUGH-INS ARE COMPLETED & GYP. BOARD IS INSTALLED. | AB. | WRITTEN DIMENSIONS HAVE PRECEDENCE OVER SCALED DIMENSIONS IN ALL CASES. G.C. SHALL VERIFY ALL DIMENSIONS AND EXISTING CONDITIONS AT THE JOB SITE AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO STARTING WORK. |
| L. | ELECTRICAL CONTRACTOR TO COORDINATE LIGHT FIXTURE LOCATIONS WITH MECHANICAL EQUIPMENT PRIOR TO INSTALLATION. | AC. | ALL DIVIDER WALL ANGLES ARE 45°, 90° OR 180° U.N.O. |
| M. | FRAMING CONTRACTOR TO COORDINATE FRAMING AROUND HVAC DUCTS, PIPES, CONDUITS AND OTHER ITEMS LOCATED ABOVE THE CEILING. | AD. | G.C. IS TO LOCATE THERMOSTATS IN LOCATIONS THAT DO NOT INTERFERE WITH DECOR. |
| N. | THERMAL AND ACOUSTICAL INSULATION IN FLOORS, WALLS AND CEILING TO COMPLY WITH STATE AND LOCAL CODE REQUIREMENTS FOR FLAME SPREAD AND SMOKE DEVELOPMENT RATINGS. | AE. | G.C. IS TO REFER TO INTERIOR ELEVATIONS FOR TYPICAL WALL FINISHES. |
| O. | ALL SHEATHING THAT IS TO RECEIVE FULLY ADHERED ROOF MEMBRANE IS TO BE ATTACHED TO METAL FRAMING BY THE USE OF NON-REVERSING SCREWS. NO NAIL FASTENERS ARE PERMITTED. | AF. | REFER TO FINISH SCHEDULE FOR EXTENT OF FINISHES AND FIXTURE WORK. |
| P. | PROVIDE TACTILE EXIT SIGNAGE AT EACH DOOR SERVING AS EXIT DISCHARGE POINTS. | AG. | PROVIDE 1/2" PLYWOOD ON WALLS TO RECEIVE FRP. |
| Q. | ALL MATERIALS SPECIFIED ARE TO BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND SPECIFICATIONS. CONTRACTOR IS TO CONSTRUCT THE PROJECT ACCORDING TO THE CONTRACT DOCUMENTS. ANY DEVIATION FROM THE INTENT OF THE CONTRACT DOCUMENTS WITHOUT ARCHITECT OR OWNER APPROVAL ARE AT THE CONTRACTOR'S OWN RISK. | AH. | ALL EXPOSED SHEATHING TO BE PAINTED IN DINING ROOM SHALL BE 1/2" GYP. BOARD. |



Christopher W. White
Architect AR #3086
5801 E. 41st St., Suite 712
Tulsa, Oklahoma

CHRISTOPHER W. WHITE
REGISTERED
ARCHITECT
No. 3086
ARKANSAS

10-29-21

Revisions:

White Design Group, P.C.
Restaurant and Interiors Consulting
 5801 EAST 41ST STREET, SUITE 712, TULSA, OKLAHOMA 74135

Arkansas

New Restaurant Conversion For:

Arby's - 1632 AR-25 Bypass

Heber Springs,

Framing Floor Plan,
Floor Plan Details, Wall
Types, General
Construction Notes

A102

Date: 10-29-21